



# CERTIFICATE OF CONFORMITY

This is to certify that

## Termimesh System™



<b>Product description</b>
Termimesh System comprises : <ul style="list-style-type: none"> <li>• <b>Termimesh stainless steel mesh</b> made from either TMA600 or TMA725 stainless steel and nominally 40 wires per inch by 30 wires per inch or 40 wires per inch by 40 wires per inch.</li> <li>• <b>Termiparge:</b> parging mixture: special purpose adhesive cement used to bond the mesh to concrete, masonry or other termite resistant substrates</li> <li>• <b>Termistop:</b> a stainless steel collar, with stainless steel clamps to be used on penetrations</li> <li>• <b>Termibond:</b> an epoxy adhesive</li> </ul>
<b>Product purpose or use</b>
The Termimesh System is a physical termite barrier. Termistop are prefabricated collars for use as physical termite barriers on slab penetrations
<b>Certificate holder</b>
TMA Corporation Pty Ltd 48 Century Road, Malaga, WA 6090 <a href="http://www.termimesh.com.au">www.termimesh.com.au</a> Tel: 08 9249 3868

**Complies with the National Construction Code 2015:**

1. Volume One: BP1.1 (b) *(limited only to actions by subterranean termites in clause BP1.1(b)(xv))*
2. Volume Two: P2.1.1 (b) *(limited only to actions by subterranean termites in clause P2.1.1(b)(xv))*

State Variation:

- Volume Two: QLD P2.1.3 *(limited only to actions by subterranean termites)*

**Subject to the following conditions and limitations:**

1. Installed by Termimesh accredited installers (holder of a current Accredited Installer Card)
2. Product installation, shall be carried out in accordance with the Termimesh System Training and Reference Manual dated Jan 07 and the specification details as listed in the index dated 01/2015.
3. The durable notice installed in accordance with NCC Volume One: B1.4 (i)(ii) and NT B1.4(i)(iii) and NCC Volume Two: 3.1.3.2(b) and QLD 3.1.3.2 (b) must be permanently fixed to the building in a prominent location, such as a meter box or the like indicating:
  - i. The method of termite risk management; and
  - ii. The date of installation of the termite management measure; and
  - iii. The manufacturer's recommendations for the scope and frequency of future inspections for termite activity.
4. When used as a termite barrier in conjunction with a concrete slab the slab must be designed and constructed according to AS 2870: 2011 or AS 3600: 2009+A1+A2.
5. When used as a termite barrier in masonry walls, the mortar joint under the barrier shall be full (have not gaps or porosity to provide an inspection zone).



JAS-ANZ



[WWW.JAS-ANZ.ORG/REGISTER](http://WWW.JAS-ANZ.ORG/REGISTER)

<b>CodeMark Certification Body</b>			10/06/2009	24/06/2015	24/06/2018	GM-CM30012 – Rev E
Global-Mark Pty Ltd, Suite 4.07, 32 Delhi Road, North Ryde NSW 2113, Australia - <a href="http://www.Global-Mark.com.au">www.Global-Mark.com.au</a>	Herve Michoux Managing Director	Unrestricted Building Certifier, Peter Gardner	Date of issue	Last update	Date of expiry	Certificate Number

This Certificate of Conformity is issued by an accredited certification body under arrangement with JAS-ANZ. The ABCB does not in any way warrant, guarantee or represent that the Product the subject of this Certificate of Conformity conforms with the BCA, nor accepts any liability arising out of the use of the Product. The ABCB disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.

It is advised to check that this Certificate of Conformity is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the ABCB website, [www.abcb.gov.au](http://www.abcb.gov.au)